


# SPECIFICATION SHEET



## ATC8055 Speaker Cable

**PACKAGE** 100m/roll

**NUMBER OF CORES** 4

### CONDUCTORS

Material Oxygen Free Copper

AWG 13

Strand Diameter 0.2 mm

Strand Quantity 80 pcs

Core Area 2.5 sq.mm

Stranding 80 x 0.2 mm

### INSULATION

Material PVC

Thickness 0.7 mm

### OUTER JACKET

Material PVC

Thickness 2 mm

### OVERALL STRUCTURE

Overall Nom. Diameter 8 mm

Overall Nom. Weight 140 g/m

### ELECTRICAL CHARACTERISTICS

Nom. Characteristic Impedance 10 Ohm/km

Nom. Capacitance Conductor to Conductor 106 pf/m

Nom. Conductor DC Resistance 10 Ohm/km

Max. Operating Voltage 500 V

### APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

EU RoHS Compliant Yes

EU RoHS Compliance Date Nov-05

ENGINEERED BY AUSTRALIAN MONITOR

Address: 1 Clyde Street, Silverwater, Sydney NSW 2128 Australia. Private Bag 149, Silverwater NSW 1811 ABN 35 007 573 417

Website: [www.australianmonitor.com.au](http://www.australianmonitor.com.au) International enquiries email: [international@australianmonitor.com.au](mailto:international@australianmonitor.com.au)

DISTRIBUTED IN AUSTRALIA AND NEW ZEALAND BY HILLS SVL [www.hillssvl.com.au](http://www.hillssvl.com.au)

NSW P: 02 9647 1411 QLD P: 07 3852 1312 ACT P: 02 6260 4544 WA P: 08 9204 0200 VIC P: 03 9890 7477 SA P: 08 8408 8300 NZ P: 09 415 9426

E: [nsw@hillssvl.com.au](mailto:nsw@hillssvl.com.au) E: [qld@hillssvl.com.au](mailto:qld@hillssvl.com.au) E: [act@hillssvl.com.au](mailto:act@hillssvl.com.au) E: [wa@hillssvl.com.au](mailto:wa@hillssvl.com.au) E: [vic@hillssvl.com.au](mailto:vic@hillssvl.com.au) E: [sa@hillssvl.com.au](mailto:sa@hillssvl.com.au) E: [sales@hillssvl.co.nz](mailto:sales@hillssvl.co.nz)