



8363

200 & 100 watt MIXER AMPLIFIER

Model 8363 is a six channel combination mixer amplifier designed and manufactured in Australia at Techcraft Sound Systems Pty Limited, to meet the needs of live performers in:—

- Clubs, hotels
- Theatre restaurants
- Schools
- Community & Civic centres
- Any applications where live entertainment performance is required.

All six input channels of the 8363 will accept high or low impedance microphones or live inputs. Each channel has separate level, bass and treble EQ controls and optional inbuilt reverberation is also available.

The 8363 provides a 200 watt RMS output for speakers at 4 ohms and is ideally suited for use with our 5085 high quality speaker system. An additional 100 watt output at 8 ohms, will provide a foldback output and can be used with our 5065 feedback wedge speaker system.

Available for rack mounting or complete with an optional vinyl covered heavy duty cabinet for portability and protection.

TECHNICAL DETAILS

Power Output	200 watts RMS mains output into 4 ohms. 100 watts foldback into 8 ohms.
Controls	Individual bass and treble EQ. Foldback send and volume. Effect/Reverb send. 3 position sensitivity switch each channel.
Mic inputs	Six balanced XLR.
Mic Sensitivity	1 Mv 600 ohms, sensitivity switch at maximum.
Aux Sensitivity	20 Mv 10 K ohms.
Signal to Noise	Better than 75 dB.
THD	Better than .1% at rated output.
Frequency Response	40 to 20,000 Hz within 3 dB.
Tone controls	± 15 dB at 100 Hz — 10 KHz (boost and cut).
Fuses	External speaker fuses (quick acting).
Dimensions	H 133 × W 484 × D 370 mm (rack mounting).
Weight	15 Kg.

