



- 24 VDC and 240 VAC operation
- Balanced 600 Ω input
- 100 v line and low impedance output
- Low profile 89mm rack height

**PRO AUDIO
POWER
AMPLIFIERS
TX300B
TX500B**

Both power amplifiers are made in Australia by Techcraft. They reflect state of the art amplifier design using toroidal power and output transformers to achieve minimum rack height and overall compact dimensions.

Ideally suited for heavy duty public address or entertainment sound reinforcement, both amplifiers feature excellent frequency response, distortion and signal to noise specifications.

Mechanically the amplifiers are solidly constructed using aluminium extrusions and generous heatsinking ensuring cool operation under continuous load conditions.

TECHNICAL SPECIFICATIONS:

SPECIFICATIONS	TX300B	TX500B
Power output	250 watt RMS	500 watt RMS
Frequency response	40 Hz to 15 Hz with + or - 3dB	
Distortion	Less than 0.5% THD at rated output	
Input sensitivity	Maximum 200 MV at 10 K ohms	
Outputs	100 volts or 4 ohms	100 volts or 2 ohms
Battery trickle charge	In discharged position 300 MA fully charged 60 MA	
Controls	LED VU meter, mains on off rocker switch with built in neon. Preset volume control screwdriver adjustable	
Dimensions	89 H x 482 W x 260 D mm	89 H x 482 W x 380 D mm
Weight	12 Kgs	15 Kgs