

# IN400



The Innovation series from AMAV is a huge step forward in the interfacing and control of audio and visual sources. Integrating a host of smart, high-end features in a compact package, the Innovation Series offers the end user simple control over complex audio visual system and AV sources. The Innovation series is as ground-breaking as it is simple to operate.

The IN400 is a compact AV switching amplifier with a host of extra features available to the AV integrator. With eight AV inputs as well as mix in, stereo line output, two composite video outputs, VGA video output, 80 watt per channel powered outputs, IR control, RS485 control and video away from audio split, the IN400 is perfect for boardroom, lecture theatre or training facility installations as a stand alone control unit, or as part of a larger system interfacing with a third party control system.

- 1RU
- On board 2 x 80 watt amplifier
- IR remote control (source select, volume and bass/treble control)
- 4 composite video/stereo audio sources
- 4 VGA (SXGA resolution)/stereo audio sources
- Mix stereo RCA audio input
- Emergency override input
- Stereo audio line level output
- 2 Composite video outputs
- VGA video output
- RS485 control
- Front panel source select and volume control with LED indication
- Bass and Treble control per source via IR and RS485 control only

# SPECIFICATIONS



<b>POWER OUTPUT (0.5%THD, 1kHz)</b>		2 x 50W @ 8 ohms
		2 x 80W @ 4 ohms
<b>THD (20-10kHz, 8ohm, -2dBr)</b>		Better than 0.1%
<b>Frequency Response(+/-3dB)</b>		20Hz-20kHz
<b>Gain</b>		24dB @ 8ohm
<b>Line Audio</b>	THD	<0.5%
	Noise Floor	-90dBu
	Frequency Response(+/-3dB)	20Hz-20kHz
	Headroom	+5dBu
<b>Video</b>	VGA	High speed RGB+Sync switching
	Video	Composite 75ohm Buffered outputs
	Video follows Audio switching	
<b>Comms</b>	Type	RS485
	Baud Rate	9600
	Number of Data Bits	8
	Parity	None
	Number of Stop Bits	1
<b>Power Consumption</b>		1/8th power 150VA (0.65A)
<b>Thermal output</b>		1/8th power 100W (341.2Btu/hr)
<b>SIZE (H X W X D)</b>		44 x 482 x 325mm or 1.75" x 19" x 12.8"
<b>NET WEIGHT</b>		7.0kg or 15.4lb
<b>SHIPPING WEIGHT</b>		9.0kg or 19.8lb
<b>SHIPPING DIMENSIONS (H X W X D)</b>		90 x 520 x 420mm or 3.5" x 19" x 16.5"

## ENGINEERED AND DISTRIBUTED BY AUSTRALIAN MONITOR

ABN 78 001 345 482 **Website:** [www.australianmonitor.com.au](http://www.australianmonitor.com.au) 1 Clyde Street, Silverwater, Sydney NSW 2128 Australia

**International enquiries email:** [international@audiotelex.com.au](mailto:international@audiotelex.com.au)

**NSW Phone:** (02) 9647 1411 **Email:** [nsw@audiotelex.com.au](mailto:nsw@audiotelex.com.au) **ACT Phone:** (02) 6260 4544 **Email:** [act@hillssvl.com.au](mailto:act@hillssvl.com.au) **VIC Phone:** (03) 9890 7477 **Email:** [vic@audiotelex.com.au](mailto:vic@audiotelex.com.au)

**QLD Phone:** (07) 3852 1312 **Email:** [qld@audiotelex.com.au](mailto:qld@audiotelex.com.au) **WA Phone:** (08) 9204 0200 **Email:** [wa@audiotelex.com.au](mailto:wa@audiotelex.com.au) **SA Phone:** (08) 8352 4444 **Email:** [sa@audiotelex.com.au](mailto:sa@audiotelex.com.au)

**NZ Phone:** (09) 415 9426 **Email:** [sales@audiotelex.co.nz](mailto:sales@audiotelex.co.nz)